Rhino 2000

Designed using the most up to date technologies, the On-Line operating systems have been developed with the clear objective of increasing all the quality and reliability parameters to the maximum, by reducing the system to a minimum size and transforming it into one of the most competitive on the market thanks to its quality, safety and ergonomics.

Potencia (W)	1400
Line in tension	230 V +/- 25%
Line out tension with line in tension	230 V +/- 2%
Line out frequency	50 Hz +/- 0,1 Hz
Line out signal / Line in tension	Sinus Wave
Type of battery	72v
Cycle of life	10´
90% battery charge time	8 hours
Communication interface	Contacts/RS232
Technology	On line,double conversion

Technical Information

Technical specifications:

On-line technology double conversion power. Professional Protection.

Perfect permanent sine wave. Filtered anda regulated continuous signal.

Built in By-Pass system.

Advanced diagnostic panel.

Protection for telephone line RJ45 (telf. / fax / ADSL / Networking).

Up to six independent outputs (according to the model).

Possibility of creating a protected dedicated line for multiple stations.

Ideal for use in multi feature servers.

Available in rack format.

Low consumption.

RS 232 communication port for the PC.

Software "DATA SAVER" with automatic shutdown in the case of power cut. Package contents:

UPS Rhino

Cables

User´s manual (7 languages)

2 years warranty card

Shipping Information

	Contains
Unity	1
Intermediate box	x
Export carton	1
Pallet	

System Requirements

Windows 7, Vista, XP or 2000

USB Port

512 MB RAM

PIII or Higher

	Unity	Intermediate box	Export carton
EAN	8436001287676	x	8436001287676
Weight			
Widht			

Depth			
Height			
Warranty	3 years		
ID de FCC/FC			